



深圳市兴华鑫电子科技有限公司

Shenzhen xinghuaxin Electronic Technology Co., Ltd

承認書

SPECIFICATION FOR APPROVAL

客戶 (Customer):

客戶料號 (Customer P/N):

興華鑫型號 (Supplier P/N):

XHxDZ-35MM 銅片-49PVC

產品名稱 (Description):

壓電陶瓷片 (piezoelectric ceramic piece)

產品規格 (Specification):

35MM 銅片-49PVC

客戶承認欄 (Customer Authorization Signature)	深圳市興華鑫電子科技有限公司 承認欄 (Supplier Audit)		
	審核	檢查	制作
	唐國興	唐玉來	吳銀娟
	日期: 2022 年 04 月 19 日 版次: A		

聲音让生活更精彩!

地址: 深圳市寶安區新安街道新樂社區新樂路 88 號廠房四層

TEL: 0755-27892904 13652428659

QQ: 438730351 2993501458

E-mail: jacky.tang@jsxhxdz.com

Http: www.jsxhxdz.com

深圳市兴华鑫电子科技有限公司

产品规格内容

Customer:			Part No:		
Product: Piezoelectric elements			XHxDZ Part No:XHxDZ-35MM 铜片-49PVC		
一、 Configuration					
Appearance and dimension: see the drawing					
Material			Piezoelectric		
Configuration			1:plane √		2:discal
Electrode form			A: fullness √		B: feedback
Metal material			T: brass √ G: stainless steel N: nickel		
二, Electrical specification					
Resonant frequency (kHz)			FS=2. 6±0. 5		
Resonant impedance (Ω)			Rr≤500Ω		
Capacitance at 1000Hz (PF)			Co=35000±30%		
Operating temperature (°C)			-20~+70		
Storage temperature (°C)			-30~+80		
Piezoelectric elements			Soldering Parameter		
Manual Soldering process			Temp.(°C)	Time(Sec.)	Times
Inclusive		silver electrode	280±10	1.5 second or less.	1~2
Lead		metal plate	320±10	2 second or less.	1~2
Lead Free		Wave soldering	260±5	4~8	2~3
	★	Manual soldering	350±10	1~3	2~3
Solder Dot: Diameter MAX 3.0mm, High MAX 1.5mm,					
Soldering sequence: 1、 silver electrode 2、 metal plate					

Remark: ★ XHxDZ Instance Soldering Process

APPEARANCE UNIT: mm±0.5

