



深圳市兴华鑫电子科技有限公司
Shenzhen xinghuaxin Electronic Technology Co., Ltd

承認書

SPECIFICATION FOR APPROVAL

客戶(Customer):

客戶料號(Customer P/N):

興華鑫型號(Supplier P/N):

XHxDZ-4540 超声波

產品名稱(Description):

喇叭(Speaker)

產品規格(Specification):

4540 超声波喇叭

客戶承認欄 (Customer Authorization Signature)	深圳市興華鑫電子科技有限公司 承認欄 (Supplier Audit)		
	審核	檢查	制作
	唐国兴	唐玉来	吴银娟
	日期: 2022 年 04 月 19 日 版次: A		

声音让生活更精彩!

地址: 深圳市宝安区新安街道新乐社区新乐路 88 号厂房四层

TEL: 0755-27892904 13652428659

QQ: 438730351 2993501458

E-mail: xhxdzsound@163.com

Http: www.jsxhxdz.com

PIEZOELECTRO TRANSDUCER SPECIFICATION

Customer:			Part No:		
Product: ultrasonic Buzzers			A&T Part No: 4540		
Technical Terms					
Resonant Frequency (KHZ)			25±5		
Rated Voltage (V _{P-P})			3.0		
Operating Voltage (V _{P-P})			1~30		
Max. Current Consumption at Rated Voltage (mA)			5.0		
Capacitance at 1000Hz (Pf)			118000±30%		
Min. Sound Output at 10cm at Rated Voltage (dB)			90		
Operating Temperature (°C)			-20~+60		
Storage Temperature (°C)			-30~+70		
Housing Material			ABS(Black)		
Environmental Protection Regulation			RoHS		
Buzzer			Soldering Parameter		
Soldering process			Temp.(°C)	Time(Sec.)	Times
Lead Free		Reflow soldering	245±15	above 180°C time 40~70	3
	★	Wave soldering	260±5	4~8	2~3
	★	Manual soldering	350±10	1~3	2~3

Remark: ★A&T Instance Soldering Process

APPEARANCE DRAWING Tol : ± 0.3 Unit: mm

